



NOTES:
 ELECTRICAL PROPERTIES:
 1.100% OPEN,SHORT & MIS-WIRE TEST
 2.CONTACT RESISTANCE: 5 ohm (MAX)
 3.INSULATION RESISTANCE: 2M ohm (MIN) 300VDC/1ms
 4.RoHS compliance.

⑦	Molding	PVC, Black, 45P	1PC
⑥	Connector	DC2.1 Socket, Nickel plated	1PC
⑤	Cable	PVC Cable,OD:6.0*3.8mm	1PC
④	Molding	PVC, Black, 45P	1PC
③	Molding	PVC, Black, 45P	1PC
②	Connector	BNC Plug, Nickel plated	2PCS
①	Connector	DC5.5*2.1 Plug, Nickel plated	1PC
NO.	PARTS NO.	Parts Name	Specification
			Q`TY

APPROVED	CHECKED	DRAWN	CUSTOMER:	NEDIS
CXD	CXD	ZHT	ITEM NO.	SEC-CABLE1020
2010.12.15	2010.12.15	2010.12.15	DRAW NO.	CB105-C051
			UNIT	mm
			SCALE	free

DESCRIPTION
 BNC/M+ DC(5.5 x 2.1)/M-BNC/M+ DC(5.5 x 2.1)/F

