

1	INTENDED USE	3
2	DESCRIPTION (FIG. A)	3
3	PACKAGE CONTENT LIST	3
4	SYMBOLS	4
5	GENERAL POWER TOOL SAFETY WARNINGS	4
5.1	<i>Working area</i>	4
5.2	<i>Electrical safety</i>	4
5.3	<i>Personal safety</i>	4
5.4	<i>Power tool use and care</i>	5
5.5	<i>Service</i>	5
6	ADDITIONAL SAFETY INSTRUCTIONS FOR DRILLS	5
7	ADDITIONAL SAFETY INSTRUCTIONS FOR BATTERIES AND CHARGERS	6
7.1	<i>Batteries</i>	6
7.2	<i>Chargers</i>	7
8	FEATURES	7
8.1	<i>Li-ion battery (5)</i>	7
9	OPERATION	7
9.1	<i>Charging the battery pack</i>	7
9.1.1	Charging indication (Fig. 1)	8
9.2	<i>Battery capacity indicator (Fig. 1a)</i>	8
9.3	<i>Inserting and removing the battery (Fig. 2)</i>	8
9.4	<i>Fitting and changing tools (Fig. 3)</i>	9
9.5	<i>Removing SDS-plus tool</i>	9
9.6	<i>Switching ON/OFF</i>	9
9.6.1	Switch lock (Fig. 4)	9
9.6.2	Direction of rotation (Fig. 5)	9
9.6.2.1	Clockwise rotation:	9
9.6.2.2	Anticlockwise rotation:	9
9.6.3	Variable speed	9
9.7	<i>Handle attachment (Fig. 6)</i>	9

9.8	<i>Depth stop</i>	10
9.9	<i>Dust collection device</i>	10
9.10	<i>Function mode selector</i>	10
9.11	<i>LED light (Fig. 7)</i>	10
9.12	<i>How to use the hammer drill</i>	10
10	CLEANING AND MAINTENANCE	11
10.1	<i>Cleaning</i>	11
10.2	<i>Maintenance</i>	11
11	TECHNICAL DETAILS	11
12	NOISE	11
13	WARRANTY	12
14	ENVIRONMENT	12
15	DECLARATION OF CONFORMITY	13

BRUSHLESS HAMMER DRILL 20V POWDP15640

1 INTENDED USE

The machine is intended for hammer drilling in concrete, brick and stone, as well as for light chiselling work. It is also suitable for drilling without impact in wood, metal, ceramic and plastic. Not suitable for professional use.



WARNING! Read this manual and general safety instructions carefully before using the appliance, for your own safety. Your power tool should only be passed on together with these instructions.

2 DESCRIPTION (FIG. A)

1. Dust cap
2. Fastening sleeve
3. Auxiliary handle
4. Function mode selector
5. On/off switch
6. Depth stop
7. Lock knob for depth stop
8. Handle
9. Forward/reverse knob
10. LED work light
11. Battery pack release button
12. Battery capacity indicator
13. Button for battery capacity indicator

3 PACKAGE CONTENT LIST

- Remove all packaging materials.
- Remove remaining packing and package inserts (if included).
- Check that the package contents are complete.
- Check the appliance, the power cord, the power plug and all accessories for transportation damage.
- Keep the packing materials as far as possible till the end of the warranty period. Dispose it into your local waste disposal system afterwards.



WARNING: Packaging materials are not toys! Children must not play with plastic bags! Danger of suffocation!









- Hammer drill
- Depth stop
- Auxiliary handle
- Dust cap
- 3 SDS drills: Ø6 & 8 & 10 x 150 mm
- SDS point chisel: 250 mm
- SDS flat chisel: 14 x 250 mm
- Instruction manual
- 1 x Battery pack
- 1 x Charger



If any parts are missing or damaged, please contact your dealer.

4 SYMBOLS

In this manual and/or on the machine the following symbols are used:

	Denotes risk of personal injury or damage to the tool.		In accordance with essential requirements of the European directive(s).
	Read manual before use.		Class II - The machine is double insulated; Earthing wire is therefore not necessary (only for charger).
	Ambient temperature 40 °C max. (only for battery).		Do not expose charger and battery pack to water.
	Use battery and charger only in closed rooms.		Do not incinerate battery pack or charger.

5 GENERAL POWER TOOL SAFETY WARNINGS

Read all safety warnings and instructions. Failure to heed warnings and follow instructions may result in electric shock, fire and/or serious injury. Keep safety warnings and instructions for future reference. The term "power tool" in the safety warnings refers to your mains-operated (corded) power tool or battery- operated (cordless) power tool.

5.1 Working area

- Keep working area clean and well lit. Untidy and dark areas can lead to accidents.
- Do not operate power tools in potentially explosive surroundings, for example, in the presence of inflammable liquids, gases or dust. Power tools create sparks which may ignite the dust or fumes.
- Keep children and bystanders at a distance when operating a power tool. Distractions can cause you to lose control of it.

5.2 Electrical safety

- Always check that the power supply corresponds to the voltage on the rating plate.
- Power tool plugs must match the outlet. Never modify the plug in any way. Do not use adapter plugs with earthed power tools. Unmodified plugs and matching outlets will reduce the risk of an electric shock.
- Avoid body contact with earthed surfaces such as pipes, radiators, kitchen ranges and refrigerators. There is an increased risk of an electric shock if your body is earthed.
- Do not expose power tools to rain or wet conditions. If water gets inside a power tool, it will increase the risk of an electric shock.
- Do not damage the cord. Never use the cord for carrying, pulling or unplugging the power tool. Keep the cord away from heat, oil, sharp edges or moving parts. Damaged or entangled cords increase the risk of an electric shock.
- When operating a power tool outdoors, use an extension cable suitable for outdoor use. Using a cord suitable for outdoor use reduces the risk of an electric shock.
- If operating a power tool in a damp location is unavoidable, use a power supply protected by a residual current device (RCD). Using an RCD reduces the risk of an electric shock.

5.3 Personal safety

- Stay alert, watch what you are doing and use common sense when operating a power tool. Do not use a power tool when you are tired or under the influence of drugs, alcohol or medication. A moment of inattention when operating a power tool may result in serious personal injury.

- Use safety equipment. Always wear eye protection. Using safety equipment such as a dust mask, non-skid safety shoes, a hard hat, or hearing protection whenever it is needed will reduce the risk of personal injury.
- Avoid accidental starts. Ensure the switch is in the off position before inserting the plug. Carrying power tools with your finger on the switch or plugging in power tools when the switch is in the on position makes accidents more likely.
- Remove any adjusting keys or spanners before turning on the power tool. A spanner or key left attached to a rotating part of the power tool may result in personal injury.
- Do not reach out too far. Keep your feet firmly on the ground at all times. This will enable you retain control over the power tool in unexpected situations.
- Dress properly. Do not wear loose clothing or jewellery. Keep your hair, clothing and gloves away from the power tool. Loose clothes, jewellery or long hair can become entangled in the moving parts.
- If there are devices for connecting dust extraction and collection facilities, please ensure that they are attached and used correctly. Using such devices can reduce dust-related hazards.

5.4 Power tool use and care

- Do not expect the power tool to do more than it can. Use the correct power tool for what you want to do. A power tool will achieve better results and be safer if used in the context for which it was designed.
- Do not use the power tool if the switch cannot turn it on and off. A power tool with a broken switch is dangerous and must be repaired.
- Disconnect the plug from the power source before making adjustments, changing accessories, or storing power tools. Such preventive safety measures reduce the risk of starting the power tool accidentally.
- Store power tools, when not in use, out of the reach of children and do not allow people who are not familiar with the power tool or these instructions to operate it. Power tools are potentially dangerous in the hands of untrained users.
- Maintain power tools. Check for misalignment or jammed moving parts, breakages or any other feature that might affect the operation of the power tool. If it is damaged, the power tool must be repaired. Many accidents are caused by using poorly maintained power tools.
- Keep cutting tools sharp and clean. Properly maintained cutting tools with sharp cutting edges are less likely to jam and are easier to control.
- Use the power tool, accessories and cutting tools, etc., in accordance with these instructions and in the manner intended for the particular type of power tool, taking into account the working conditions and the work which needs to be done. Using a power tool in ways for which it was not intended can lead to potentially hazardous situations.

5.5 Service

- Your power tool should be serviced by a qualified specialist using only standard spare parts. This will ensure that it meets the required safety standards.

6 ADDITIONAL SAFETY INSTRUCTIONS FOR DRILLS

- Hold power tools by insulated gripping surfaces when performing an operation where the cutting tool may contact hidden wiring. Contact with a "live" wire will make exposed metal parts of the tool "live" and shock the operator.
- Let bit cool before touching, changing or adjusting it. Bits heat up dramatically while in use, and can burn you.
- Avoid unintentional starting. Prepare to begin work before turning on the tool.
- Do not lay the tool down until it has come to a complete stop. Moving parts can grab the surface and pull the tool out of your control.
- When using a handheld power tool, maintain a firm grip on the tool with both hands to resist starting torque.

- Do not leave the tool unattended when the Battery Pack is connected. Turn off the tool, and remove the Battery Pack before leaving.
- The battery Charger gets hot during use. The Charger's heat can build up to unsafe levels and create a fire hazard if it does not receive adequate ventilation, due to an electrical fault, or if it is used in a hot environment. Do not place the Charger on a flammable surface. Do not obstruct any vents on the Charger. Especially avoid placing the Charger on carpets and rugs; they are not only flammable, but they also obstruct vents under the Charger. Place the Charger on a stable, solid, non-flammable surface (such as a stable metal workbench or concrete floor) at least 1 foot away from all flammable objects, such as drapes or walls. Keep a fire extinguisher and a smoke detector in the area. Frequently monitor the Charger and Battery Pack while charging.
- This product is not a toy. Keep it out of reach of children.
- The warnings, precautions, and instructions discussed in this instruction manual cannot cover all possible conditions and situations that may occur. It must be understood by the operator that common sense and caution are factors which cannot be built into this product, but must be supplied by the operator.
- Make sure of your footing on ladders and scaffolding when drilling free-handed.
- Use a line detector to localize lines in walls with concealed electric, water or gas lines. Avoid touching live components or conductors.
- Wear ear muffs to protect your hearing. Loss of hearing can be a gradual process!
- Wear goggles and use a dust mask on jobs generating dust.
- Do not use in areas where there are vapours or flammable liquids.
- Chisel bits and drill bits may be flung out of the machine accidentally and cause serious injury:
 - Before starting to work, always check that the chisel or drill bit is properly locked in the chuck.
 - Examine the chuck regularly for signs of wear or damage.
 - Never start up a hammer tool until it pressed against a workpiece (wall, ceiling, etc.).
 - Protect your eyes and other workers from flying particles and splinters. Wear a helmet! Set up partition walls!
 - Wear work gloves to protect fingers from bruising and grazing.
 - Vibrations can injure the hand-arm system. Keep exposure to vibrations as short as possible.

7 ADDITIONAL SAFETY INSTRUCTIONS FOR BATTERIES AND CHARGERS



Use only batteries and chargers applicable for this machine.

7.1 Batteries

- Never attempt to open for any reason.
- Do not store in locations where the temperature may exceed 40 °C.
- Charge only at ambient temperatures between 4 °C and 40 °C.
- Store your batteries in a cool dry place (5 °C-20 °C). Never store batteries in discharged state.
- It is better for Li-ion batteries to discharge and reload them regularly (at least 4 times a year). The ideal charge for long-term storage of your Li-ion battery is 40% of capacity.
- When disposing of batteries, follow the instructions given in the section "Protecting the environment".

- Do not cause short circuits. If connection is made between the positive (+) and negative (-) terminal directly or via accidental contact with metallic objects, the battery is short circuited and an intense current will flow causing heat generation which may lead to casing rupture or fire.
- Do not heat. If batteries are heated to above 100 °C, sealing and insulating separators and other polymer components may be damaged resulting in electrolyte leakage and/or internal short circuiting leading to heat generation causing rupture or fire. Moreover do not dispose of the batteries in fire, explosion and/or intense burning may result.
- Under extreme conditions, battery leakage may occur. When you notice liquid on the battery, proceed as follows:
 - Carefully wipe the liquid off using a cloth. Avoid skin contact.
 - In case of skin or eye contact, follow the instructions below:
 - ✓ Immediately rinse with water. Neutralize with a mild acid such as lemon juice or vinegar.
 - ✓ In case of eye contact, rinse abundantly with clean water for at least 10 minutes. Consult a physician.



Fire hazard! Avoid short-circuiting the contacts of a detached battery. Do not incinerate the battery.

7.2 Chargers

- Never attempt to charge non-rechargeable batteries.
- Have defective cords replaced immediately.
- Do not expose to water.
- Do not open the charger.
- Do not probe the charger.
- The charger is intended for indoor use only.

8 FEATURES

8.1 Li-ion battery (5)

Advantages of Li-ion batteries:

- Li-ion batteries have a higher capacity/weight ratio (more power for less heavy, more compact, battery).
- No memory effect (capacity loss after several charge/discharge cycles) like other type batteries. (Ni-Cd, Ni-MeH,...).
- Limited self-discharge (also see chapter: Storage).

9 OPERATION

9.1 Charging the battery pack

The battery pack for this tool is supplied in a low charge condition to prevent possible problems; therefore, you have to charge the battery before first use.



Note: Batteries will not reach full charge the first time they are charged. Allow several cycles for the item to fully charge. The battery should only be charged indoors.

After normal use, about 1 hour of charging time is required for the battery to be fully charged. The battery pack will become slightly warm while charging; this is normal and does not indicate a problem.

Do not place the charger in an area of extreme heat or cold. Best is at normal room temperature. When the battery becomes fully charged, unplug your charger from the power supply and remove the battery pack from the charger.

Note:

1. Allow the battery pack to cool completely before charging
2. Inspect the battery pack before charging; do not charge a cracked or leaking battery pack.

9.1.1 Charging indication (Fig. 1)

Connect the charger to the power outlet socket:

- Solid green: ready to charge.
- Flickering red: charging.
- Solid green: charged.
- Solid green and red: battery or charger damaged.



Note: If the battery does not fit properly, disconnect it and confirm that the battery pack is the correct model for this charger as shown on the specification chart. Do not charge any other battery pack or any battery pack that does not securely fit the charger.

1. Frequently monitor the charger and battery pack while connected.
2. Unplug the charger and disconnect it from the battery pack when finished.
3. Allow the battery pack to cool completely before using it.
4. Store the charger and battery pack indoors, out of reach of children.



NOTE: If battery is hot after continuous use in the tool, allow it to cool down to room temperature before charging. This will extend the life of your batteries.



NOTE: Remove battery pack from charger stand which use your thumb or fingers, press the battery's release button in and pull the battery pack off at the same time.

9.2 **Battery capacity indicator (Fig. 1a)**

There are battery capacity indicators on the battery pack; you can check the capacity status of the battery if you squeeze the button (12). Before using the machine, please press switch trigger to check if the battery is full enough for properly working.

Those 3 LED might show the status of the capacity level of the battery:

3 LED's are litt: Battery fully charged.

2 LED's are litt: Battery 60% charged.

1 LED is litt: Battery almost discharged.

9.3 **Inserting and removing the battery (Fig. 2)**



WARNING: Before making any adjustments ensure the drill is switched off with the direction of rotation selector in the centre position

- Remove the battery: press the battery release latch in and at the same time pull the battery pack off.
- To insert the battery, push the battery pack onto the contacts of the tool.

9.4 **Fitting and changing tools (Fig. 3)**

The device is equipped with a SDS-plus attachment system.

- Clean tools and grease with a thin layer of machine grease before fitting.
- Fit the desired bit into the bit holder.
- Push and rotate the dust-free tool into the tool holder as far as it will go. The tool will lock automatically.
- Check that it has locked by pulling the tool

9.5 **Removing SDS-plus tool**

Pull back fastening sleeve, hold and remove tool.



**Accessories can be hot after use. Don't touch the tip of accessory by hand!
Please always use protective gloves to remove accessories.**

9.6 **Switching ON/OFF**

- Switching on: Press the operating switch (5).
- Switching off: Release the operating switch (5).



Note: The trigger switch can be used as a variable speed control mechanism.

9.6.1 Switch lock (Fig. 4)

The switch trigger can be locked in the centre position.

This helps to reduce the possibility of accidental starting when not in use. To lock the switch trigger, place the direction of rotation selector in the centre position.

9.6.2 Direction of rotation (Fig. 5)

Direction of rotation is controlled by the direction of rotation selector located above the switch trigger.

9.6.2.1 **Clockwise rotation:**

Right: To select forward rotation, release the on/off switch and push the forward/reverse lever to the left side of the tool.

9.6.2.2 **Anticlockwise rotation:**

Left: To select reverse rotation, push the lever to the right side of the tool.

9.6.3 Variable speed

This tool has a variable speed switch that delivers higher speed and torque with increased trigger pressure.

Speed is controlled by the amount of switch trigger depression.

9.7 **Handle attachment (Fig. 6)**

For reasons of safety, only use the hammer drill with handle attachment.

You will be able to obtain a safe body position when working by rotating the handle attachment. Loosen and turn the handle attachment in an ant-clockwise direction. Slip loop onto the neck of the housing tool and position the handle, then tighten the handle attachment.





9.8 Depth stop

Loosen the handle attachment and place the straight part of the depth stop in the hole. Adjust the depth stop and retighten the handle attachment.

9.9 Dust collection device

Before carrying out hammer-drilling work vertically overhead pull dust collecting device over the drill bit.

9.10 Function mode selector

	<p>Hammer/ drill mode: Drill in masonry, concrete and natural stone. Don't use the hammer drill function for ceramic tile or others material cannot withstand impact energy.</p>
	<p>Chiselling mode: Chisel in masonry, concrete and natural stone.</p>
	<p>Drilling mode: Drilling in wood, synthetic materials and metal.</p>
	<p>Chisel Rotation: Non-working position used only to rotate flat chisel into the desired position.</p>



Important! Hammer drilling requires a low pressure. Too much pressure will place unnecessary load on the motor. Check the drill bits regularly. Re-sharpen or replace blunt drill bits.



Do not use the chuck with SDS connector in combination with the hammer/hammer drill function!

9.11 LED light (Fig. 7)

The LED work-light can light prior to motor running if you press the switch lightly, which keep the work area to be lighted for checking clearly at first, and it lights also during your operation.



WARNING: Do not stare directly at the light beam. Never aim the beam at any person or an object other than the work piece.



Do not deliberately aim the beam at personnel and ensure that it is not directed towards the eye of a person for longer than 0.25 s.

9.12 How to use the hammer drill

- After placing the tip of the tool on concrete surface, switch ON.
- By utilizing the weight of the machine and by firmly holding the hammer drill with both hands, one can effectively control the subsequent recoil motion.
- Proceed at a moderate work-rate, the use of too much force will impair efficiency.
- The hammer drill function will not work when the tool does not encounter resistance.



CAUTION After long time of use, the cylinder case becomes hot. Therefore, be careful not to burn your hands.



WARNING Don't apply big pressure to the machine. The hammer mechanism is activated by applying a slight pressure on the tool when the chisel bit is in contact with the work-piece.

10 CLEANING AND MAINTENANCE

10.1 Cleaning

- Keep the ventilation slots of the machine clean to prevent overheating of the engine.
- Regularly clean the machine housing with a soft cloth, preferably after each use.
- Keep the ventilation slots free from dust and dirt.
- If the dirt does not come off use a soft cloth moistened with soapy water.
- Never use solvents such as petrol, alcohol, ammonia water, etc. These solvents may damage the plastic parts.

10.2 Maintenance

- Our machines have been designed to operate over a long period of time with a minimum of maintenance. Continuous satisfactory operation depends upon proper machine care and regular cleaning.

11 TECHNICAL DETAILS

Rated voltage	20 V
Electric motor type	Brushless
Rotation speed	0-1350 min ⁻¹
Drill capacity concrete	22 mm
Drill capacity steel	13 mm
Drill capacity wood	30 mm
Impact rate	0-4750 strks/min
Impact force	3 J
4 functions	
Second handle type	Adjustable auxiliary handle
Soft grip	Yes
Motor winding material	Copper

12 NOISE

Noise emission values measured according to relevant standard. (K=3)

Acoustic pressure level LpA	86dB(A)
Acoustic power level LwA	97dB(A)



ATTENTION! Wear hearing protection when sound pressure is over 85 dB(A).

aw (Vibration)	10.5m/s ²	K = 1.5 m/s ²
----------------	----------------------	--------------------------

13 WARRANTY

- This product is warranted for a 36-month period effective from the date of purchase by the first user.
- This warranty covers all material or production flaws excluding : batteries, chargers, defective parts subject to normal wear & tear such as bearings, brushes, cables, and plugs, or accessories such as drills, drill bits, saw blades, etc. ; damage or defects resulting from maltreatment, accidents or alterations; nor the cost of transportation.
- Damage and/or defects resulting from inappropriate use also do not fall under the warranty provisions.
- We also disclaim all liability for any bodily injury resulting from inappropriate use of the tool.
- Repairs may only be carried out by an authorised customer service centre for Powerplus tools.
- You can always obtain more information at the number 00 32 3 292 92 90.
- Any transportation costs shall always be borne by the customer, unless agreed otherwise in writing.
- At the same time, no claim can be made on the warranty if the damage of the device is the result of negligent maintenance or overload.
- Definitely excluded from the warranty is damage resulting from fluid permeation, excessive dust penetration, intentional damage (on purpose or by gross carelessness), inappropriate usage (use for purposes for which the device is not suitable), incompetent usage (e.g. not following the instructions given in the manual), inexpert assembly, lightning strike, erroneous net voltage. This list is not exhaustive.
- Acceptance of claims under warranty can never lead to the prolongation of the warranty period nor commencement of a new warranty period in case of a device replacement.
- Devices or parts which are replaced under the warranty therefore remain the property of Varo NV.
- We reserve the right to reject a claim whenever the purchase cannot be verified or when it is clear that the product has not been properly maintained. (Clean ventilation slots, carbon brushes serviced regularly, etc.).
- Your purchase receipt must be kept as proof of date of purchase.
- Your appliance must be returned undismantled to your dealer in an acceptably clean state, (in its original blow-moulded case if applicable to the unit), accompanied by proof of purchase.
- Your tool must be charged at least 1x per month to ensure optimal operation of this tool.

14 ENVIRONMENT



Should your appliance need replacement after extended use, do not dispose of it with the household refuse, but in an environmentally safe way.

Waste produced by electrical machine items should not be handled like normal household rubbish. Please recycle where recycle facilities exist. Check with your Local Authority or retailer for recycling advice.

15 DECLARATION OF CONFORMITY



VARO – Vic. Van Rompuy N.V. - Joseph Van Instraat 9 - BE2500 Lier - BELGIUM,
declares that,

Product: Brushless hammer drill 20V
Trade mark: POWERplus
Model: POWDP15630

is in conformity with the essential requirements and other relevant provisions of the applicable European Directives, based on the application of European harmonized standards. Any unauthorized modification of the apparatus voids this declaration.

European Directives (including, if applicable, their amendments up to the date of signature):

2011/65/EU
2006/42/EC
2014/30/EU

European harmonized standards (including, if applicable, their amendments up to the date of signature):

EN60745-1 : 2009
EN60745-2-6 : 2010
EN55014-1 : 2017
EN55014-2 : 2015

Keeper of the Technical Documentation: Philippe Vankerkhove, VARO – Vic. Van Rompuy N.V.

The undersigned acts on behalf of the company CEO,

Ludo Mertens
Regulatory Affairs – Compliance Manager
22/09/20