KÖNIG ELECTRONIC

Your World,
Our Technology

Quattro LNB

Multikytkimelle

Esittely:

- Erittäin matala kohinaluku

Yleistä:

Ylivoimainen König Quattro LNB vain 0.6 dB signaali/kohinasuhteella !
Erityisen sopiva paikkoihin jossa tarvitaan suurinta mahdollista signaalivoimakkuutta ja -laatua.

Tekniset tiedot:

• Feed diameter:	40 mm
• Outlet:	4 (HH/HV/LH/LV)
• RF input:	Low: 10.7 ~ 11.70 GHz High: 11.7 ~ 12.75 GHz
• IF output:	Low: 950 ~ 1950 MHz High: 1100 ~ 2150 MHz
• Local oscillator:	Low: 9.75 GHz High: 10.6 GHz
• Stability:	± 3 MHz (max.) @ -40°C ~ +60°C
• Noise figure (typ.):	Low: 0.6 dB High: 0.6 dB
• Cross polarization (typ.):	20 dB
• DC current cons. max:	250 mA
• Operating voltage:	11.5 ~ 21 V DC
• Band switching:	Low: 0 Hz High: 22 KHz ± 4 KHz
• Temperature range:	-55°C~ +80°C

Myynti-info:

Tilauskoodi:	**LNB1-QUATTROKN**
Malli:	Universal quattro LNB
Pakkaus:	Ltk
TARIC koodi:	8543709099

CE

5 412810 146123

	Erä	LxWxH (mm)	Paino
Yksi	1 kpl	190x170x080	297 g
Ltk	20 kpl	395x380x380	7.1 kg

©2011 König®. All rights reserved. König® is a registered trademark.
Specifications are subject to modification without prior notice. Contents may differ slightly from what is shown.
König can not be held responsible, nor liable for the information contained in this document.